



Concorde Battery Corporation

2009 San Bernardino Road, West Covina, CA 91790 USA | Telephone (626)813-1234 | Fax (626)813-1235

TECHNICAL BULLETIN

Subject: Electrolyte Content Chairman® Batteries

January 25, 2013

Number AGM-1

All Chairman® batteries offered by Concorde Battery Corporation are classified as Valve Regulated Lead Acid (VRLA) batteries. According to Section 608 of the International Fire Code (2006), spill containment is not required for VRLA batteries regardless of the size. However, for VRLA battery systems having an electrolyte capacity of more than 50 gallons, an approved method and material for neutralization of electrolyte spills must be provided. The method and material must be capable of neutralizing a spill of 3 percent of the electrolyte capacity of the largest VRLA cell or block in the room to a pH between 7.0 and 9.0.

The table shown on the second page of this Technical Bulletin provides the electrolyte content (gallons of electrolyte) of all Chairman® battery models offered by Concorde Battery. These numbers may be used to calculate the total electrolyte volume for a given battery installation using the following formula:

Total Electrolyte Volume = Electrolyte Volume per Battery X No. Batteries

Neutralization materials are available from various sources; see the following links for examples:

<http://www.acran.com/>

<http://www.egsintl.com/>

Note that there may be different state and local requirements depending on the exact location of the battery installation. It is the responsibility of the battery system provider to ensure that the battery installation complies with all applicable codes and regulations.

NOTICE: *The data/information contained herein has been reviewed and approved for general release on the basis that this document contains no export controlled information.*

DISCLAIMER: *The technical data contained herein is based upon the best information available as of the latest revision date. Concorde Battery Corporation makes no warranty of merchantability, fitness for any particular purpose, or any other warranty, expressed or implied, with respect to such information, and we assume no liability resulting from its use. It is the obligation of each user of the product to determine the suitability for any particular application and to comply with the requirements of all applicable laws regarding use and disposal of this product.*



Concorde Battery Corporation

2009 San Bernardino Road, West Covina, CA 91790 USA | Telephone (626)813-1234 | Fax (626)813-1235

Electrolyte Volumes of Chairman® Series Batteries

Part Number	Gallons of Electrolyte*
AGM-1234T	0.38
AGM-1240T	0.46
AGM-1248T	0.81
AGM-1255T	0.64
AGM-1265T	0.99
AGM-1280T	0.92
AGM-1285T	1.22
AGM-12100T	1.11
AGM-12105T	1.26
AGM-12115T	1.38
AGM-12125T	1.50
AGM-12148T	1.88
AGM-12210L	2.19
AGM-12255L	2.52
AGM-6100T	0.63
AGM-6220T	1.35
AGM-6300T	1.87
AGM-6400HT	2.54
AGM-2660T	1.35
AGM-2900T	1.87
AGM-21200HT	2.54

*Specific gravity of electrolyte when battery is fully charged ranges from 1.28 to 1.36.

NOTICE: The data/information contained herein has been reviewed and approved for general release on the basis that this document contains no export controlled information.

DISCLAIMER: The technical data contained herein is based upon the best information available as of the latest revision date. Concorde Battery Corporation makes no warranty of merchantability, fitness for any particular purpose, or any other warranty, expressed or implied, with respect to such information, and we assume no liability resulting from its use. It is the obligation of each user of the product to determine the suitability for any particular application and to comply with the requirements of all applicable laws regarding use and disposal of this product.