




1. MANUFACTURED AND INSPECTED IAW AS9100 QUALITY SYSTEM REQUIREMENTS.
2. ABBREVIATION USED IN TITLE IS: VALVE REGULATED SEALED LEAD ACID (VRSLA).
3. SEE DRAWING NO. CB-00274 AND PROCEDURE P-1000 FOR ASSEMBLY AND TEST INSTRUCTION. PROCEDURES AND ASSEMBLY DRAWINGS ARE FOR INTERNAL USE ONLY.

4. BATTERIES ARE RATED IAW INTERNATIONAL ELECTROTECHNICAL COMMISSION STANDARD 60952-1 AND RTCA DO-293, UNLESS OTHERWISE NOTED.

REVISIONS			
REV	DESCRIPTION	DATE	APPROVED
A	UPDATED NOTES 1, 2, 5, AND RATINGS PER TSO TEST	11/6/09	JBT
B	ADDED CG WITH DIMS, DELETED NOTES 1 & 6, RENUM NOTES 2 THRU 5	4/8/10	JBT



PART NUMBER	RG-47
MAXIMUM WEIGHT	43 LBS [19.5 KG]
RATED CAPACITY, C ₁	17 AH
POWER RATING AT 23°C	I _{pp} 900 A, I _{pr} 625 A
POWER RATING AT -18°C	I _{pp} 600 A, I _{pr} 425 A
POWER RATING AT -30°C	I _{pp} 450 A, I _{pr} 300 A



ENVELOPE DRAWING

		CAGE CODE	PART OR IDENTIFYING NO.		NOMENCLATURE OR DESCRIPTION			MATERIAL SPECIFICATION			ITEM NO.
QTY	REQD	PARTS LIST									
UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES TOLERANCES ARE: FRACTIONS DECIMALS ANGLES ± 1/32 .XX ± .06 ± 1' .XXX ± .030				CONTRACT NO.		CONCORDE BATTERY CORPORATION 2009 SAN BERNARDINO RD, W. COVINA, CA 91790					
				APPROVALS	DATE						TITLE BATTERY, VRSLA, 24 VOLT
				DRAWN	JBT	4/27/99					
				TREATMENT	NONE	CHECKED	AMIII	10/5/99			
FINISH	NONE	APPROVED	JBT	10/18/99	SIZE	CAGE CODE	DWG NO.	REV			
SIMILAR TO		ACT WT	CALC WT	ISSUED	JJ	4/12/10	SCALE	1/2	SHEET	1 OF 1	